

COMPAÑÍA NACIONAL DE ABRASIVOS, S.A. DE C.V.

PLANTA: AVENIDA 1 DE MAYO No. 1801 ORIENTE ZONA INDUSTRIAL TOLUCA, MEX. C.P. 50071

CONMUTADOR: (722) 548-03-30 VENTAS 548-03-40 FAX. 216-08-12

EMAIL: cinasatol@prodigy.net.mx

www.cinasa.com.mx





SAFETY DATA SHEET

Section I - Chemical Product and Company Information

| Product Name | Vitrified Bonded Abrasive Products ITEM # W0313 |
|----------------|--|
| Trade Name | Grinding Wheels |
| | Cia. Nacional de Abrasivos S.A. de C.V. |
| Manufacturer | Av. Primero de Mayo 1801 Ote. |
| ivianutacturei | Zona Industrial |
| | Toluca, Edo. de México 50071 |
| Phone Number | 722 5480330 |
| Fax Number | 722 5480349 |
| Effective Date | July, 2017 |

Section II - Composition Information on Ingredients

| Chemical Name | CAS# | ACGIH TLV | OSHA PEL | NIOSH | Carc. Y/N | Max. % |
|-----------------------------|-----------|---------------------|----------------------|--------------------|--------------|--------|
| Aluminum Oxide | 1344-28-1 | 10 mg/m^3 | 15 mg/m^3 | NA | N | 95 |
| Glass or Glass / Porcenlain | NA | 10 mg/m^3 | 15 mg/m ³ | 5 mg/m^3 | N | 40 |

| HMIS Hazard Rating | |
|---------------------|---|
| Health | 0 |
| Flammability | 0 |
| Reactivity | 0 |
| Personal Protection | Е |



COMPAÑÍA NACIONAL DE ABRASIVOS, S.A. DE C.V.

PLANTA: AVENIDA 1 DE MAYO No. 1801 ORIENTE ZONA INDUSTRIAL TOLUCA, MEX. C.P. 50071

CONMUTADOR: (722) 548-03-30 VENTAS 548-03-40 FAX. 216-08-12

EMAIL: cinasatol@prodigy.net.mx

www.cinasa.com.mx







Section III - Hazards Identification

| Emergency Overview: | Dust may be irritating. May cause delayed lung damage. Low hazard to usual industrial or commercial handling. |
|---------------------|---|
| Target Organs: | Respiratory System |
| Inhalation: | Grinding generates dust. Prolonged exposure to grinding dust may cause respiratory probelms or aggravate existing conditions. Inhalation during grinding can cause coughing and shortness of breath. Consideration should also be given to the airborne concentration of the material being ground. |
| Eye Contact: | Dust generated during grinding may irritate eyes. |
| Skin Contact: | Excessive contact with dust may cause irritation. |
| Ingestion: | No known effects but ingestion is not recomended. |
| Other: | Some grinding operations may cause noise or vibration irritation. Grinding wheels are not a know carcinogen. |

Section IV - First Aid Measures

| Eyes: | Immediately flush with plenty of water. Get medical attention if |
|-------------|--|
| | irritation persists. |
| Skin: | Wash skin with soap and water. Get medical attention if |
| | irritation persists. |
| Inhalation: | Move to fresh air. |
| Other | If hearing problems persist, obtain medical assistance if |
| | neccesary. |

Section V - Fire Fighting Measures

| Section 1 The Lighting Measures | | |
|---------------------------------|---|--|
| Flash Point: | None | |
| Flammable Limits: | None | |
| Extinguishing Media: | Any media appropriate for the sorrounding fire. | |
| Fire Fighting Equipment: | Fire fighters should wear gloggles and self - contained breathing | |
| The Figuring Equipment. | apparatus to avoid inhalation of smoke or vapors. | |
| | None from this product. Consideration must be given to the | |
| Fire and Explosion | potential fire / explosion hazards from the material being | |
| Hazards: | processed. May materials create flammable / explosive dust | |
| | when ground. | |

Section VI - Accidental Release Measures

| Clean Up: | Use normal clean up procedures. |
|-----------|--|
| Disposal: | Dispose of in accordance with local, state and federal regulation. |



COMPAÑÍA NACIONAL DE ABRASIVOS, S.A. DE C.V.

PLANTA: AVENIDA 1 DE MAYO No. 1801 ORIENTE ZONA INDUSTRIAL TOLUCA, MEX. C.P. 50071

CONMUTADOR: (722) 548-03-30 VENTAS 548-03-40 FAX. 216-08-12

EMAIL: cinasatol@prodigy.net.mx

www.cinasa.com.mx







Section VII - Handling and Storage

| Handling: | Do not use at speeds greater than product was made to be used. |
|-----------|--|
| | Inspect wheel for damage on arrival and prior to mounting on |
| | machine. Avoid breathing dust. Avoid skin and eye contact with |
| | grinding dust. Use in well ventilated area. |
| | Wheels should not be exposed to water or other solvents; any |
| Storage | temperature or humidity condition that causes condesation on |
| _ | the wheels or freezing temperatures. See ANSI B7.1,2.3. |

Section VIII - Exposure Controls / Personal Protections

| Sterion (1111 Emposition | ontions / 1 ersonar 1 rote enoug |
|--------------------------|--|
| | Use NIOSH approved respirators as required to maintain |
| Respiratory Protection: | exposure below Threshold Limit Values (TLV/TWA). See |
| | OSHA 29 CFR 1910.134. |
| Skin Protection: | Leather, cloth, rubber or vinyl gloves as desired by user. |
| Eye Protection: | Safety goggles or safety glasses with side shields are recommended. See OSHA 29 CFR 1910.133. |
| Hearing Protection: | See OSHA 29 CFR 1910.215 concerning hearing protection. |
| Engineering Controls: | Local exhaust ventilation as necessary to keep dust levels below Threshold Limit Values (TLV/TWA). |
| Other Precautions: | Visually inspect all wheels before mounting for possible damage. Do not operate above maximum operating speed. Always use a guard. Refer to ANSI B7.1 for the "Safety Requirements for the Use, Care and Protection of Abrasive Wheels." |

Section IX - Physical and Chemical Properties

| Section 1A - 1 hysical and Chemical I Toper des | | |
|---|---------------|--|
| Boiling Point; | NA | |
| Vapor Pressure: | NA | |
| Vapor Density: | NA | |
| Specific Gravity: | 1.5 - 3.1 | |
| Solubility in Water: | Very slightly | |
| Freezing Point: | NA | |
| Melting Point: | NA | |
| рН: | Not Relevant | |
| Physical Form: | Solid | |
| Color: | Various | |
| Odor: | None | |



COMPAÑIA NACIONAL DE ABRASIVOS, S.A. DE C.V.

PLANTA: AVENIDA 1 DE MAYO No. 1801 ORIENTE ZONA INDUSTRIAL TOLUCA, MEX. C.P. 50071

CONMUTADOR: (722) 548-03-30 VENTAS 548-03-40 FAX. 216-08-12

EMAIL: cinasatol@prodigy.net.mx

www.cinasa.com.mx







Section X - Stability and Reactivity

| Stability (Conditions to | This is a stable material. Avoid overspeed and unsafe use |
|---------------------------|--|
| Avoid): | conditions. |
| Incompatibility (Specific | Avoid strong acids and bases. |
| Materials to Avoid): | |
| Hazardous Polymerization: | Will not occur. |
| | Dusts are generated in use. In most cases, dusts from the |
| Hazardous Decomposition: | workpiece will be significantly greater than from the grinding |
| | wheel. Coolants may produce other decompositon products. |

Section XI - Toxicological Information

| No Information Available |
|--------------------------|
| |

Section XII - Ecological Information

No Information Available

Section XIII - Disposal Considerations

Dispose of in accordance with local, state and federal regulations.

Section XIV - Transport Information

Grinding wheels are not a DOT hazardous material.

Section XV - Regulatory Information

This product does not contain and was not manufactured with any Ozone Depleting Chemicals.

Section XVI - Other Information

The information and recommendations set forth are taken from sources believed to be accurate. Cia. Nacional de Abrasivos, S.A. de C.V. makes no warranty with respect to the accurancy of this information or the suitability of these recommendations, assumes no liability to any user thereof. It is the responsability of the user to investigate and understand pertienent sources of information to comply with all laws and procedures applicable to the safe use and handling of the product and to determine the suitablity of the product for it's intended use.