



## HG3 Hollow Grinder Specifications

<b>Stock #:</b>	HG3
<b>Knife Blade Capacity:</b>	Any length blade
<b>Grinding Wheels:</b>	Consist of two 6" (15.2cm) aluminum oxide straight cupped grinding wheels mounted as a set on two shafts rotating in the same direction
<b>Wheel Dresser:</b>	(2 each) semi-automatic air over hydraulics
<b>Motor:</b>	(2 each) 1.0 HP, 3 Phase, 208-230/460 Volt, 60 HZ, 1140 RPM 208-230 Volt - 9 amps Total 460 Volt - 4.5 amps Total
<b>Electrical Requirements:</b>	3 Phase, 208-230/460 Volt
<b>Air Requirements:</b>	85 PSI (586kPa) with quick disconnect
<b>Cooling System:</b>	Self-contained recirculating water with USDA approved additive
<b>Dimensions:</b>	49" H x 33" W x 22" D (125cm x 84cm x 56cm)
<b>Product Weight:</b>	385 lbs. (175kg)
<b>Shipping Weight:</b>	515 lbs. (234kg)

TRU HONE CORPORATION

1721 NE 19th Avenue, Ocala, FL 34470 USA

USA Canada 1.800.237.4663 \* All Others 352.622.1213 \* Fax 352.622.9180

TruHone.com \* info@TruHone.com

4/16/2018