



## HR8 Honer Specifications

<b>Stock #:</b>	HR8
<b>Knife Blade Capacity:</b>	Any length blade
<b>Honing Wheels:</b>	Consist of six 8" (20.3cm) aluminum oxide honing wheels mounted as a set (assembled) on two contra-rotating shafts
<b>Wheel Dresser:</b>	(2 each) semi-automatic air over hydraulics
<b>Motor:</b>	(2 each) 0.75 HP, 3 Phase, 208-230/460 Volt, 60 HZ, 1140 RPM 208-230 Volt - 8 amps Total 460 Volt - 4 amps Total
<b>Motor Control:</b>	Adjustable Speed Frequency Drive Parameters P100 - 01 P102 - 28.5 P110 - 01 P121 - 13 P122 - 15 P134 - 60
<b>Electrical Requirements:</b>	3 Phase, 208-230/460 Volt
<b>Air Requirements:</b>	85 PSI (586kPa) with quick disconnect
<b>Cooling System:</b>	Self-contained recirculating water with USDA approved additive
<b>Dimensions:</b>	46" H x 33" W x 22" D (117cm x 84cm x 56cm)
<b>Product Weight:</b>	370 lbs. (168kg)
<b>Shipping Weight:</b>	500 lbs. (227kg)

### TRU HONE CORPORATION

1721 NE 19th Avenue, Ocala, FL 34470 USA

USA Canada 1.800.237.4663 \* All Others 352.622.1213 \* Fax 352.622.9180

TruHone.com \* info@TruHone.com

5/23/2018